

Options and Versatility



The 8580 and 8590 Vehicle-mount computers from Psion Teklogix give you multiple options and complete versatility. Use these rugged Windows® XP Professional / Windows® XP Embedded computers to take your native Windows® XP client into the demanding warehouse environment.



ADVANTAGES

Easy Key Access

- Multiple key options (4, 10 or 25 keys) allow complete customization to the specific application environment.
- The ergonomic location of the keys simplifies user interaction with robust software applications.

Enhanced Connectivity

- Multiple connectivity options including RS232, Ethernet and two USB 2.0 ports allow for connecting a wide range of peripherals including barcode and RFID scanners or printers.

Environment Controller

- A built-in environment controller monitors various parameters on the 8580/8590 to ensure optimal performance.

High Resolution Screen

- Run native warehouse management application clients without modification to the user interface with the high XGA resolution (1024 x 768) of the 8590.
- Improved screen visibility in all lighting conditions can be achieved by upgrading the 8590 display brightness to 800 nits.

Latest Industrial Technologies and Standards

- A standard PCIe MiniCard is used for WLAN connections. The processor board corresponds to the XTX standard.

Large Selection of Accessories

- Psion Teklogix offers a full range of peripherals and support for a complete solution.

8580/8590 Vehicle-Mount Computers

Specifications*



8580/8590



PROCESSOR & MEMORY

- Intel 800 MHz Celeron M standard
- Intel 1 GHz Celeron M option
- 512MB or 1GB RAM option

OPERATING SYSTEM

- Microsoft Windows® XP Professional
- Microsoft Windows® XP Embedded

STORAGE OPTIONS

- CF Card, 1, 2, 4 or 8 GB
- 20 GB HDD (automotive)

DISPLAYS & TOUCH SCREEN

8580

- 4, 10 or 25 keys on front
- Resolution: SVGA 800x600
- Size: 10.4" diagonal
- 400 nits display brightness
- Resistive analogue touch screen

8590

- 4, 10 or 25 keys on front
- Resolution: XGA 1024x786
- Size: 12.1" diagonal
- 450 nits display brightness
- 800 nits optional high bright display for usage in sunlight intensive applications (25 keys only)
- Resistive analogue touch screen

ENCLOSURE

8580

- Dimensions: 9" x 11" x 3.2" (229 mm x 280 mm x 83 mm)
- Weight: 8.8 lb (4.0 kg)

8590

- Dimensions: 10.3" x 12.6" x 3.9" (262 mm x 319 mm x 99 mm)
- Weight: 10.4 lb (4.7 kg)

INDICATORS

- Power On LED
- HDD
- Temperature warning

POWER SWITCH

- On/Off switch on the device
- Automatic switch off via software or ignition signal for a proper shut down

SOUND

- SoundBlaster 16 compatible on-board Sound Card

RADIO

- 2.4 GHz 802.11b/g PCIe MiniCard

EXPANSION

- 1 x Compact Flash Slot Type I or II (3.3V).
- 1 x PCIe MiniCard
- PCI card slot option
- Cardbus slot option

INTERFACES

- 2 x full function UART (DB9). COM1 with either 0, 5 or 12V on pin 9 for external devices
- 2 x USB 2.0 host ports
- 1 x Ethernet 10/100 RJ45
- 1 x PS/2 Port (keyboard/mouse)

ENVIRONMENTAL

- Standard operating temperature range:

8580

-4°F to 122°F (-20°C to 50°C)

8590

14°F to 122°F (-10°C to 50°C)

- Optional freezer operating temperature range: -22°F to 122°F (-30°C to 50°C)
- Humidity (operating): 10% to 90% RH non-condensing at 104°F (40°C)
- IEC 60529 dust & water protection enclosure rating IP66/IP67
- Shock & vibration testing IEC 60721-3-5 - Class 5M2 (HDD version), Class 5M3 (CF card version)
- MIL-STD-810F

POWER SUPPLY & MANAGEMENT

- 24 - 48V power input range
- 12V power input
- 110/220V external power supply
- Power consumption: typically 30W, max 100W (freezer version)

OPTIONAL ACCESSORIES

- Vehicle mount/cradle
- Terminal emulation software (TekTerm)
- Antennas
- Keyboards
- Pre regulator
- RFID scanner
- Bar code scanner
- Printers

APPROVALS

- FCC Part 15 Subpart B, Class B, Emissions
- Industry Canada ICES-003 Class B
- EN 55022:1998, Class B Emissions
- EN 55024:1998 Immunity
- EN 60950-1, UL 60950-1, CSA 22.2 No. 60950-1, Safety
- ISO7637-1/2 Vehicle transients



Product is RoHS compliant

*Specifications are subject to change without notification.

Psion Teklogix™ is a trademark of Psion Teklogix Inc. Other product ranges mentioned in this document may be trademarks of Psion Teklogix Inc. or trademarks or registered trademarks of other software, hardware, or service providers and are used herein for identification purposes only.