

Xerox 6279[™] Wide Format Big-time productivity and flexibility



Employ the printer that works as hard as you do.

Introducing the Xerox 6279 Wide Format Printer. The easy to operate, flexible, and amazingly efficient way to improve the productivity of your demanding CAD environment. Whether you're producing architectural plans, engineering renderings, schematics, or other wide format applications, the 6279 gives you the image quality you need and the speed you demand.

The speed to get more done. From the moment you turn it on, the 6279 – and its new, intuitive colour user interface – is all about efficiency. With its ability to print 9 D/A1-size prints per minute and scan up to while printing, you can meet even the most demanding deadlines. Plus, it holds up to four rolls of bond paper, tracing paper, or film for uninterrupted printing and unmatched media flexibility.





Printer only



Sharp images.

Your important prints, scans, and copies deserve nothing less than superior image quality. That's why the 6279 offers crisp 600 x 600 dpi printing and 600 x 600 dpi scanning capability. So even your most complex monochrome prints – including engineering and architectural renderings and schematics – can have sharp, precise detail print after print. And with the optional On-Board Scanner or Wide Format Scan System, copies of worn originals are improved with automatic background suppression.

Enhanced flexibility.

With a wide range of confi guration options – including Printer-only and Copier/Printer with monochrome scanning that is upgradeable to colour – and its integrated Xerox FreeFlow® Accxes® Print Server, the 6279 is designed to fit seamlessly into any workflow. To protect your investment, the software and equipment are field-upgradeable, so your system can grow with your business. By adding the optional scan-tonet key, you can add additional versatility, such as scanning multi-page PDFs and multi-page TIFFs, and enable remote colour workfl ows with TotalAccxess. Its complete set of drivers ensures you can print graphics, business, and engineering applications and support a wide range of file formats, including PostScript®, PDF, DWF, BMP, JPEG, PNG, GIF, and DGN.

Outstanding reliability.

You need a printer that works every time you need it. And the 6279 is designed to do just that. Built on proven Xerox technology and more than 50 years of product innovation, you can count on it to provide uncompromised durability and reliability day in and day out. Plus, it's backed by our award-winning, 24/7 service and support – giving you increased peace of mind.

The total support your need.

Xerox supports your entire solution, from printer to media and consumables. A worldwide network of service professionals is always ready to help you make the most of your Xerox solution, and help you grow your business.

Designed for demanding wide format applications like these:

- Architectural or construction plans
- Architectural or engineering renderings
- Schematics
- Electrical diagrams (e.g. wiring)
- Mechanical 2D

- Solids modeling
- Mechanical 3D
- Scientific/Medical
- Seismic
- GIS/Mapping



User interface is intuitive, easy-to-use, and interactive, enabling a fast learning curve.



Integrated Xerox FreeFlow AccxesPrint Server.



Xerox FreeFlow
Accxes print driver
interface is designed
for production-level
performance.



Choice of standard 2-Roll and optional 4-Roll or 2-Roll/2-Tray configurations allow for uninterrupted printing and greater media flexibility.



Optional colourcapable scannerseither On-Board Scanner or Xerox Wide Format Scan System – enable colour workflows.



Scan-to-mailbox, FTP, or remote printer options available for added functionality.

2

Xerox 6279

Wide Format Solution

Print Engine

Process/Imaging

• Xerographic LED

Print Engine Speed

• 105 mm/sec (4.1 ips)

Prints/Minute

• 9 D/A1 pages per minute

FPOT

• <19 sec (Roll 1, D/A1 size)

FCOT

• <23 sec (Roll 1, D/A1 size)

FreeFlow® Accxes®

• Max. copies 999

Initial Warm-up Time

• 3 min

Media Supply

- 1 drawer, 2 rolls
- 2 drawers, 4 rolls (optional)
- 2 Cut Sheet Feed Trays with 2 rolls (optional)
- Standard Manual Sheet Inserter

Output Size

- Min: 279.4 mm (11")
- Max: 914.4 mm (36")

Resolution

• 600 dpi

Grayscale Levels

• 256 simulated monochrome only

User Interface

•381 mm (15") full colour touch screen

Media

Media Types

Bond, tracing paper, film

Media Weights

- Bond: 60-110 a/m2 (18-20 lb.)
- Tracing Paper: 90–112 g/m² (20 lb.)
- Film: 75-100 micron (4 mil)

Optional On-Board Scanner System

Scanner Speed

- Monochrome Scanning: 152.4 mm/sec. (6 ips)
- Colour Scanning (optional) 50.8mm/sec. (2ips)

Scanner Resolution

in new ways with measurable results. Descriptions in this material of

improvements. Plea:

printing ink. Windo

of Novell, Inc. in the

a registered trader

Company. Other co

machine production

• 600 dpi

Grayscale

• 256 levels

Colour (optional)

24-bit

Maximum Document Input Size

- 945 mm (37.2") width x 15 m (49.2') (Monochrome input)
- 945 mm (37.2") width x 7.5 m (24') (Colour input)
- 914.4 mm (36") width (image)

Maximum Document Thickness

• 12.7 mm (0.5")

Registration

• Right side

Electronic Collation

• 999

Output Stacking Capacity

- 100 D (A1)
- Generic Folder Interface (GFI)

FreeFlow® Accxes® Print Server

Internal

- Memory 2 GB or better
- Hard Disk Drive 80 GB or better

Ports

• IEEE1394 (Wide Format Scan System only), Serial RS232 (service only), and USB 2.0 (device interface only)

Network Protocols

• TCP/IP 10/100/1000: LPR: TFTP

Data Formats

- Standard: HPGL/2 (HP 750C emulation), HP-RTL (HP 750C emulation), TIFF 6.0 (including LZW), CALS 1&2, CalComp 906/907/951/PCI, FileNET, NIRS, CGM, VCGL, VRF, Versatec Data Standards. Xerox Emulation 150, C4, JPEG
- Optional: Adobe [®] Postscript[®] 3[™], PDF (1.6), DWF, BMP, JPEG 2000, PNG, GIF, DGN

Job Accounting

• Account Data Tracking (optional)

Applications

- FreeFlow® Accxes® Document Submit
- FreeFlow [®] Accxes [®] Document Retrieve

perties of papers or

gistered trademark

c. Post Script is

Hewlett-Packard

• Account Management Tool

- Concurrent print, copy and scan-to-file (with select options)
- Web Printer Management Tool
- InstantAccxes
- Scan to multi-page PDF (with select option)
- Scan to multi-page TIFF (with select option)

Windows® Printer Drivers

• XP, 2000, Server 2003, XP x64, Server 2003 x64, Server 2008 (both 32 and 64 bit), Vista®, Vista® x64, Windows 7(both 32 and 64 bit)

Electrical Requirements

Print Engine

• 240 V +/- 10 %, 50 Hz, A

Wide Format Scan System

- 240 V (A) +/- 10 %, 50 Hz FreeFlow® Accxes®
- 240 V (A) +/- 10 %, 50Hz

Dimensions and Weight (Width, Depth, Height, Weight)

6279 Printer

- 1,550 mm (61"), 847 mm (33.3"),
- 1.400 mm (55.1")
- 2-Roll: 258 kg (570 lbs)
- 4-Roll: 295 kg (651 lbs)
- 2-Roll/2-Tray: 323 kg (711 lbs)

6279 Printer with On-Board Scanner

- 1,550 mm (61"), 847 mm (33.3"), 1.400 mm (55.1")
- 2-Roll: 300 kg (663 lbs)
- 4-Roll: 337 kg (744 lbs)
- 2-Roll/2-Tray: 365 kg (804 lb)

Xerox Wide Format Scan System

• 1,345 mm (53"), 1,348 mm (53.07"), 1,168 mm (45.9"), 68 kg (150 lbs)





Additional logos here

Protecting the environment is fundamental to our commitment to corporate citizenship. Fuji Xerox Australia provides products that have been designed with both our customers and the environment in mind. We are known for our end-of-life product resource recovery and remanufacturing programs. Our products regularly lead the industry in energy performance and all our sites maintain ISO 14001:2004 Environmental Management System Certification. Fuji Xerox Australia has been recognised for its achievements in environmental sustainability by the United Nations and the Banksia Environmental Foundation in Australia.

Reproduction Prohibitions Please note that reproduction of the following is prohibited by law:

Domestic and overseas bank notes and coins, government-issued securities, national bonds and local bond certificates. Unused postage stamps and post cards. Certificate stamps stipulated by law. The reproduction of works for copyright purposes (literary works, musical works. paintings, engravings, maps, cinematographic works, photographic works, etc.) is prohibited except when they are reproduced personally, at home or within limited range according to the above. This product is equipped with an anticounterfeit feature. This feature is not intended to prevent illegal reproduction. Be extremely careful about the management of equipment used.



Before using the product, read the Instruction Manual carefully for properuse. Use the product with an appropriate adequate power source and voltage displayed. Be sure to establish a ground. In the case of a failure or short circuit, an electric shock may result.

For more information or detailed product specifications,

Fuji Xerox Australia Pty Ltd. ABN 63 000 341 819. Australian Head Office: 101 Waterloo Rd, Macquarie Park NSW 2113. Phone (02) 9856 5000 Fax (02) 9856 5003

13 14 12

www.fujixerox.com.au

FUJI Xerox

Fuji Xerox Australia is part of a world leading enterprise for business process and document management services. Through

Other trademark info here

NOTE: IF there are no additional trademarks then move the "About Fuji Xerox Australia" paragraph to bottom of margin

Spares for the standard configuration of installed machines is supported for up to 7 years from the date of the end of

the implementation of efficient business processes and effective communication, we deliver the right information to the right people in the right format. A continuous source of innovation helps us optimise IT and print infrastructures to deploy document strategies that are efficient, productive and waste-free. This enables our customers to meet their business challenges