





DATA SHEET




HANYOUNG HOIST, FOOT, MAIN SWITCH


HOIST / FOOT / MAIN SWITCH

HOIST SWITCH


Model	HY-1022 (2 BUTTON)	HY-1024 (4 BUTTON)	HY-1026 (6 BUTTON)	HY-1028 (8 BUTTON)
Appearance				
Protection construction	IP-65 (IEC)			
Material	Case	ABS		
	Screw	Stainless screw		
Color	Button packing	Special rubber (black)		
	Cable bracket	Special rubber (black)		
Insulation resistance	Min. 100 MΩ (At d.c 500 V)			
Dielectric strength	1500 V a.c for 1 minute			
Ambient temperature	-15 °C ~ 45 °C			
Ambient humidity	45 ~ 85 %R.H.			

FOOT SWITCH

Model	HY-101	HY-102
Appearance		
Rated voltage	250 V a.c, 6 A	250 V a.c, 6 A
Internal switch	HY-P601 A	HY-P601 A
Material of case	ABS resin	AL Diecasting

Model	HY-103	HY-104	HY-105
Appearance			
Rated voltage	250 V a.c, 10 A		
Internal switch	HY-P701D		HY-P701B
Material of case	AL Diecasting		

MAIN SWITCH

Appearance	Suffix code	Rated insulation voltage	Rated current	Material
	MAS-025-A · B	690 V a.c	25 A	Anti-flammable
	MAS-063-A · B		63 A	
	MAS-125-A · B		125 A	