

# E25 Series - Hand Held Cable Fault Locators

## TRANSCAT®

[Visit us at Transcat.com!](http://www.transcat.com)

35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001



- Thumb wheel adjustable balance to cancel out transmitted pulse
- Impedance: **E2520** - 120Ω, **E2521** - 50Ω and **E2522** - 40Ω
- Humidity: 0 to 93% RH at +40°C
- Instant response keys
- User friendly intuitive interface
- Ability to change the velocity factor during test
- Accuracy: ±1% of range
- Weight: 0.6kg (with batteries)
- Mains/AC blocking filter
- VF: 0.01 to 0.99 in steps of 0.01 - adjustable during test
- Resolution: 1% of range
- Automatic power down
- 28 X 64 graphic LCD with contrast control for optimum viewing
- Auto or fixed ranging

### Ranges:

**E2520** - 100m, 300m, 1000m, 3000m and auto

**E2521** - 10m, 30m, 100m, 300m and auto

**E2522** - 10m, 30m, 100m, 300m and auto

full product  
datasheet

## TRANSCAT®

[Visit us at Transcat.com!](http://www.transcat.com)

35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001