










Universal baths – SUB series

Universal water baths, high quality and excellent temperature stability for a wide range of routine applications.

- Ambient + 5°C to 99°C operation
- Stability ± 0.2°C
- Wide range of options to suit different applications
- Robust durable design, with electronic control



Options and accessories

	 SUB6 6 L	 SUB14 14 L	 SUB28 28 L	 SUB36 36 L
	Gabled lids*			
	LU6	LU14	LU28	LU36
	Direct condensation away from immersed vessels, avoid contamination and reduce evaporation			
	Flat lids*			
	LF6 (2 ring sets)	LF14 (4 ring sets)	LF28 (6 rings sets)	LF36 (8 ring sets)
	With ring sets of variable hole diameter to accommodate tall vessels whilst reducing evaporation			
	Polypropylene spheres* (packs per bath)			
	1 x PS20	1 x PS20	2 x PS20	3 x PS20
	Useful alternative to a lid, minimises evaporation and heat loss whilst allowing easy access to vessels in the bath; particularly useful for tall vessels			
	Raised shelves			
	–	RS14H – covers half the area of SUB14	RS28H – covers half the area of SUB28	RS36H – covers half the area of SUB36
	Provide two alternative depths to accommodate different sizes/shapes of vessels simultaneously. More than one shelf can be used to achieve a range of depths			
	Racks (no. per bath)			
	1 x J2	2 x J2	4 x J2	6 x J2
	Choice of 8 variants to accommodate different tube diameters and microtubes (see page 9.6)			
	Base trays			
	SBT6	SBT14	SBT28	SBT36
	Required if flat-bottomed flasks are to be placed directly on the base of the bath			

* lid or spheres should be used above 60°C



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)1245 600560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.