






P+ Digital Back Overview

P 65+ Camera System

	P 65+	P 40+	P 45+	P 30+	P 25+
Description	World's first full frame medium format digital back, featuring Sensor+ with a choice of 60.5 megapixels for finest resolution or scaled full frame captures for fast workflow and low light versatility.	Fastest digital back with up to 1.8 fps in Sensor+ mode. A choice of 40 or 10 megapixels and an ISO range from 50 to 3200 makes this digital back the most versatile tool in the range.	High resolution shooter with unlimited burst sequences and optimized for large format photography with live preview functionality for easy composition and focus checking.	The top quality fast fashion shooter with ISO 1600, with superior moiré control and well suited for harsh environments.	All-round shooter with unlimited burst sequences and optimized for large format photography with live preview functionality for easy composition and focus checking.
Sensors					
Lens Factor	1.0	1.3	1.1	1.3	1.1
CCD size effective	53.9 x 40.4 mm	43.9 x 32.9	49.1 x 36.8	44.2 x 33.1	48.9 x 36.7
Active pixels	8984 x 6732	7320 x 5484	7216 x 5412	6496 x 4872	5436 x 4080
Pixel size (micron)	Full res. 6 x 6 Sensor+ 12 x 12	Full res. 6 x 6 Sensor+ 12 x 12	6.8 x 6.8	6.8 x 6.8	9 x 9
Resolution (megapixels)	60.5 15.0	40 10	39	31.6	22
Light sensitivity (ISO)	50-800 200-3200	50-800 200-3200	50-800	100-1600	50-800
Exposure time	1/10,000 – 1 minute	1/10,000 – 1 minute	1/10,000 sec. up to one hour with XPose+ technology		
Image quality	16bit-OptiColor+, 12 f-stops Dynamic+ and Lens+ technology				
Capture time (frames per sec.**)	1.0 1.4	1.2 1.8	0.67	0.8	0.67
Battery Lifetime (up to captures/up to stand-by time*)	2000 / 3	2500 / 4	2500 / 4	3000 / 4	4000 / 4
Image buffer	1.3 GB High Speed RAM	1.3 GB High Speed RAM	640 MB high speed RAM		
Display	2.2" QVGA TFT with 230,000 pixels, high brightness and contrast both indoor and outdoor, very fine details				



The world's most desirable camera system

The Phase One P 65+ Camera system is designed to be a seamless extension of your creativity. Extraordinary capture becomes natural through ease of use and direct control.

Take advantage of the Phase One digital focal plane lenses or Schneider Kreuznach leaf shutter lenses. You can also use your Mamiya 645 AF/AFD or Hasselblad V lenses for an even broader choice.

Being the benchmark for reliability and image quality, the P 65+ digital back ensures that you amaze your clients at every capture. The P 65+ offers the world's first full frame 645 sensor, delivering astounding 60.5 megapixel captures and giving you full advantage of your medium format lenses.

Sensor+ technology marks another milestone offering ultimate flexibility with scalable pixels for higher sensitivity and faster workflow.

Results are based on testing in Phase One's testing department. Variation may be expected due to specific camera set up. Battery used for test is new 2500mAh Li+.
 *) standby Time will vary a lot depending on temperature, usage of battery and state of the back e.g. Zero Latency will increase power consumption significantly
 **) Maximum expected performance. The actual performance will be dependent on the camera model and on the camera and digital back capture modes content is subject to change without notice

Your local Phase One partner

P 65+ Digital Back Specifications



Inset image © Drew Gardner

- Sensor+ technology solution
- 15 mega pixel captures for faster workflow and higher sensitivity
- 60.5 mega pixel captures for astounding level of details
- Extreme 12.5 f-stops dynamic range
- True wide angle performance
- 100% viewfinder area for best composition
- Up to 1.4 frame per second capture rate

Imaging technology	
CCD	Full frame CCD
Lens Factor	1.0 / Full frame
Resolution	60.5 mega pixels
Active pixels	8984 x 6732 pixels
CCD size effective	53.9 mm x 40.4 mm
Pixel size	6 x 6 micron
Image ratio	4:3
Dynamic range	12.5 f-stops

P 65+ full resolution capture mode	
Resolution	60.5 mega pixels
Pixel size	6 x 6 micron
RAW file compression	IIQ large: 60 MB IIQ small: 40 MB
ISO	50, 100, 200, 400, 800

Sensor+ capture mode	
Resolution	15 mega pixels
Pixel size	12 x 12 micron
RAW file compression	IIQ large: 15 MB IIQ small: 10 MB
ISO	200, 400, 800, 1600, 3200

Output files	
Color depth	16 bit per color
Image file formats	All output formats of Capture One are possible: TIFF-RGB, TIFF-CMYK, JPEG
Color management	RGB, Embedded ICC profile, CMYK

LCD screen	
Size	2.2"
Resolution	230,400 pixels
Viewing angle	160°

Lighting	
Supports all photographic lights: Flash, tungsten, daylight, fluorescent, HMI	

Operating conditions	
Temperature	0° to 40°C (32° to 122°F)
Humidity	15 to 80% RH (non-condensing)

Computer minimum requirements	
Mac	Fast Intel Core™ 2 Duo or later CPU, 4 GB RAM, Fast HDD: RAID 0 configured systems for max performance, Nvidia 8800 series graphics card or newer
PC	Intel® Pentium® 4, 2 GB RAM, 10 GB free hard disk space, IEEE 1394 interface, Windows XP®, Service Pack 3 or Windows Vista®, Service Pack 1

P+ back mounts	
Phase One/ Mamiya	Phase One 645DF/AF, Mamiya 645DF/AFD, RZ67 Pro IID and Mamiya RB67es, Mamiya RZ67 PRO IID via adaptor
Phase One H101	Hasselblad H1 and H2
Hasselblad V	Hasselblad 555ELD, 553ELX, 503CW and 501CM Via adaptor: Mamiya RZ67 Pro II Mamiya RB67
Contax	Contax 645

Wide angle & technical cameras	
4 x 5" via FlexAdaptor: Arca Swiss, Cambo, Linhof, Toyo, Sinar, Plaubel, Horseman.	

Storage files	
Phase Ones IIQ RAW file format speeds up the image capture and file transfer. It increases the storage capacity by turning the full 16 bit image data into a compact RAW file format. The default IIQ RAW-large format is completely lossless.	

Software	
Capture One 4.8.3 or later	

Certifications	
CE	

content is subject to change without notice

645DF Camera Body Specifications



- Open platform for maximum choice and compatibility
- Durable, proven platform for secure operation
- Ergonomic handling and ease of use
- Use Phase One digital lenses, Mamiya AF/AFD lenses or Hasselblad V lenses
- Guaranteed up to 300.000 captures or 3 years (VA)
- Exposures from 1/4000s to 60 minutes
- Flash synchronization up to 1/1600 sec.

Shutter speed from 1/4000s to 60 minutes, B and X modes can match the extreme long exposure capability of the P+ digital backs or stop action with fast shutter speed or flash.

The mirror and viewfinder of the Phase One 645DF camera are almost three times larger than those of 35mm cameras, providing much greater control of focus and composition.

While hosting a complete list of features and custom functions, the Phase One 645DF camera is extremely easy to use. All settings important to the exposure are easily controlled by manual dials and soft buttons.

Camera type	Modular 645 AF SLR body
Lenses	Phase One Digital focal plane lenses, Schneider Kreuznach leaf shutter lenses and Mamiya 645 AFD lenses Compatible with Hasselblad V lenses
Backs	Open platform back mount
Auto focus	TTL phase-difference AF with 3 focus points Focus confirmation in manual mode Infrared AF assists for unfailing focus Auto focus lock for swift AF/ M shift
Shutter	1/4000s to 60 minutes Up to 2 fps Shutter speed bracketing
Flash	Focal plane shutter: Up to 1/125s Leaf shutter lenses: Up to 1/1600s' 1 st and 2 nd curtain flash synchronization X sync terminal and support for TTL flash
Light Metering	TTL metering (average, spot and auto) Programmable AEL button Exposure compensation: +/- 5EV
Mirror-Up	Electronically-activated by switch on grip

Viewfinder	Fixed prism viewfinder Exchangeable diopter from -5 to +3 LCD panel with full exposure information
Focusing Screen	Interchangeable focus screens Laser engraved mask for digital back Matte, Grid, Checker, Microprism
Selftimer	Self-timer from 2 to 60 sec
Remote	Screw-in cable release on shutter button Terminal for electronic triggering devices
Stop Down Preview	Stop down button on front of camera
Tripod Socket	1/4 inch and 3/8 inch included
Power Requirements	6 AA batteries (standard or rechargeable) External battery pack – 6 AA batteries External AC adapter
User configuration	3 Custom dial modes for capture settings 36 custom settings Customizable dials and buttons
Size	W, H, D // 6, 5, 7.2" // 153, 128, 184mm
Weight	35 oz. / 1030g. w/o batteries

content is subject to change without notice