

## U-17



**AG Neovo's most eco-minded display with unmatched durability and power efficiency in a stylish design ideal for the busiest multi-user environments.**

With a bright 17-inch screen, stereo speakers, side-mount headphone jack and USB port, the U-17's multimedia feature set is matched only by its breakthrough power-saving technology. Reduce power consumption up to 50% compared to standard LCD monitors (67% versus CRTs), or cut power usage to zero with EcoSwitch. Add durable touch-sensor controls, best-in-class NeoV™ Optical Glass, and the U-17 easily becomes the smartest, most eco-friendly choice of professionals.

- > NeoV™ Optical Glass
- > Contemporary & professional design
- > 1280 x 1024 resolution, 1000:1 contrast ratio and 3ms response
- > Eco-friendly: Slash CO<sub>2</sub> emissions up to 50%; Recyclable materials and green design
- > Energy efficient: Cut power bills up to 50%; Zero-watt consumption with EcoSwitch
- > Built-in headphone jack and stereo speakers
- > Wear-resistant touch sensor controls
- > Easy-access USB port (pass through)
- > New intuitive OSD with settings lock
- > Dual PC inputs: VGA and DVI
- > Kensington® security socket
- > VESA standard wall mount



NeoV™ Optical Glass - The most trusted hard glass protection available.  
Only on AG Neovo displays

# U-17

## Specifications

## U-17

<b>Panel</b>	Panel Type Panel Size Max. Resolution Pixel Pitch Brightness Contrast Ratio Viewing Angle (H/V) Display Colour Response Time	TFT LCD 17.0" (432 mm) SXGA 1280 x 1024 0.264 mm 250 cd/m <sup>2</sup> (Typical) 1000:1 (Typical) 170°/160° (Typical) 16.7M 3 ms (GTG)z
<b>Frequency (H/V)</b>		H: 24 kHz - 81 kHz V: 56 Hz - 75 Hz
<b>Input</b>	Analogue Digital	15-Pin D-Sub 24-Pin DVI-D
<b>Audio</b>	Audio In Audio Out Speaker	3.5 mm Audio Line-in 3.5 mm Headphone Jack 1W x 2
<b>Power</b>	Power Supply Power Requirements Consumption	Internal AC 100 - 240 V, 50 - 60 Hz < 20 W (On) < 0.5 W (Stand-by) < 0.5 W (Off) = 0 W (EcoSwitch off)
<b>NeoV™ Optical Glass</b>	Thickness Reflection Rate Transmission Rate Coating Hardness	3.0 mm (0.12") < 1% > 96% > 9H
<b>Plug &amp; Play</b>	VESA	DCC 2B, DDC/CI
<b>Operating Conditions</b>	Temperature Humidity	0 °C ~ 40 °C 10% ~ 90%
<b>Storage Conditions</b>	Temperature Humidity	-20 °C ~ 60 °C 5% ~ 95%
<b>Mounting</b>	VESA FPMPMI	Yes (100 x 100mm)
<b>Tilt</b>	Tilt	0° ~ +20°
<b>Dimensions</b>	Product (W x H x D) Packaging (W x H x D)	397 x 390 x 174 mm (15.6" x 15.4" x 6.9") 480 x 460 x 145 mm (18.9" x 18.1" x 5.7")
<b>Weight</b>	Product Packaged	5.7 kg (12.5 lbs) 7 kg (15.4 lbs)
<b>Regulation Approval</b>	Certifications & Compliance	CB, FCC, CE, GOST-R, WEEE, Energy Star, RoHS, REACH
<b>Accessories</b>	Supplied	CD ROM (user manual and drivers), audio cable, AC power cord and 15-Pin D-Sub cable



Side-mount headphone jack, USB port and built-in stereo speakers for multimedia convenience



Durable, long-lasting touch sensor controls won't wear out like mechanical buttons



NeoV™ Optical Glass protects against scratches, impacts and other physical damage



Slash power bills and CO emissions by up to 50% (67% versus CRTs); EcoSwitch cuts power usage to zero when off

